

# ∞ Infinity Spot M



## KEY FEATURES

---

- “MULTI-lamp” concept ready
- New superfast zoom mode, from 42° down to 9°
- Bright as a 1200 W fixture, in a package 1/3 the size and 60% of the power
- Space, weight, power saving
- Fully equipped effects engine
- Artnet ready
- New digital ballast technology
- Superior dimming
- Superior cmv

## SPECIFICATIONS

---

- CMY color mixing
- 5 colors + open
- CTO filter
- 1 aerial wheel, 7 gobos + open
- 1 break-up wheel, 7 gobos + open
- 2 rotating prisms
- Film frame effect
- Focus
- Proportional zoom 9° - 42°
- Proportional frost
- Iris
- Dimmer
- Mechanical and electronic strobe (zap effect), synchronized, random, pulse effect
- Modular design for easy maintenance and servicing
- Pan 540°, Tilt 284°, 16 bit

## PHYSICAL SIZE

---

- Length: 459 mm (18.1 in)
- Width: 377 mm (14.8 in)
- Height: 602 mm (23.7 in), head straight up
- Weight: 27 kg (59.2 lbs)

## LAMP AND BALLAST

---

- Type: Philips MSR Gold 575/2, Philips MSR Gold 700/2,
- Mini FastFit, MULTI-lamp ready
- Color temperature: 7400 Kelvin
- Color rendering index: 71
- Average lamp life: 750 hours
- Socket: PGJX28
- Digital electronic ballast with Power Factor Correction

## CONTROL PROTOCOL AND PROGRAMMING

---

- USITT DMX512/1990
- Artnet, Artnet to DMX converter
- DMX channels: 23/24
- Setting and addressing: LCD display or remotely
- RDM ready

## ELECTRICAL SPECIFICATIONS/ CONNECTIONS

---

- AC power: 90 – 250 V, auto sensing, 50/60 Hz, 2 m (6.6 ft) integral cable without power plug
- Power consumption: 4.5 A at 230 V, 9.5 A at 115 V
- DMX data in/out: 3 pin and 5 pin locking XLR
- Ethernet RJ45 port