## MC-Showtime Specifications

## Description

MC-Showtime controls four or more MX-x scanners (MX-1 or MX-4, depending on the MC-Showtime model you have) automatically, manually, or using any or all of the 30 supplied 6-scene sequences. MCShowtime can also control CX-color changers, as well as Synchrozap QX250 and Acrobat intelligent effects.

Hardware	Installation
Housing: aluminum	Table top
Built-in microphone	Flush mount
7-button 2-digit display	Rack mount
3-PIN female XLR data out connection	
Physical	AC Supply
Size (L x W x H): 143 x 114 x 78 mm	Input: 3-prong IEC male socket
(5.6 x 4.5 x 3.1 in)	EU: 220 - 250 V / 50 Hz
Weight: 1 kg (2.2 lb)	US: 110 - 120 V / 60 Hz
Playback Facilities	Trig Sources
30 different 6-scene sequences	Sound
Easy execution of shows	Automatic
Slow, medium, fast and auto-selection of show	Manual
Blackout, strobe and manual override	
Included items	Accessories
1.5-meter IEC power cable 5-meter 3-pin XLR data cable	19 in (48.26 cm) rack mount plate for 1 controller
3-pin male XLR termination plug User manual: P/N 35000097	19 in (48.26 cm) rack mount plate for 2 controllers