

Specifications

Physical

Length	455mm
Width	285mm
Height.....	280mm
Dry weight	11.9Kg

Performance

Effect coverage	2500m ³ /min
Operating time	continuous
Warm up time	6-8 minutes
Safety device.....	DTP device

Control and programming

Control options	DMX (optional accessory), timer remote
DMX channels	1

Fluid system

Capacity	3.8 litre
Fluid consumption	10.5ml/min
Compatible fluids	Pro Haze

Connections

DMX (optional accessory).....	3 pin XLR
Remote / machine link	RJ45 x2
AC power input	IEC plug

Electrical

AC voltage	120V / 230V, 50/60Hz
Main fuse (120V US version)	10AT
Main fuse (230V EU version)	6.3AT
Pump fuse (230V /120V)	3.15AT
Power usage (120V US version)	920W (8A)
Power usage (230V EU version)	920W (4.15A)

Thermal

Maximum ambient temperature (Ta max).....	40°C (104°F)
Exterior surface temperature, steady state, at 20°C ambient	40°C (104°F)

Approvals

European EMC:.....	EN61000-6-3,EN61000-3-2,EN61000-3-3,EN50366
European safety:	EN 60 335-1,EN 50366
Immunity:	EN61000-6-1, EN61000-4-2,EN61000-4-3
ETL approvals (cETLus).....	UL60335-1, CSA-E60335-1(Pending)

Included items

EU Model:

3m(9.8ft) IEC power cable 3x1.0mm² with no male connector

US Model:

2m(6.5ft) US power cable 18AWG with US male connector(UL approved)

1 x fluid container (empty)

Accessories

DMX decoder moduleP/N 91612011

Ordering information

Martin Magnum 2500HZ 120VP/N 92225400

Martin Magnum 2500HZ 230VP/N 92225450

Martin Magnum 2500HZ Remote controlP/N 92765033