

iProfile Flex



iProfile Flex - # 9124/1
(1 unit in single flight case)

iProfile Flex- # 9124/2
(2 unit in double flight case)

SPECIFICATIONS

- «Best Color»™ (Exclusive Coemar Patent): colors dynamically determine the output of the lamp, thus allowing an optimal level of light output to be maintained
- CMY color mixing
- 5 colors + open
- Proportional CTO filter
- 1 aerial wheel, 6 rotating gobos + open
- 2 rotating prisms
- 2 rotating animation wheels
- Framing system: four blades framing system - creation of various geometric shapes (triangle, quadrilaterals, rectangles) - images rotation
- Focus
- Proportional zoom 7.4° - 26.5°
- Iris
- Dimmer
- Mechanical and electronic strobe (Zap effect), synchronized, random, pulse effect
- Modular design for easy maintenance and servicing
- Pan 500°, Tilt 252°, 16 bit

PHYSICAL SIZE

- Length: 545 mm (21.46 in)
- Width: 495 mm (23.43 in)
- Height: 930 mm (36.61 in), head straight up

- Weight: 56.7 kg - (125 lbs)

LAMP AND BALLAST

- Type: Philips MSR 2000 SA
- Color temperature: 6000 Kelvin
- Color rendering index: > 80
- Average lamp life: 750 hours
- Socket: GY 22
- Electronic ballast with Power Factor Correction
- Electronically adjustable lamp power (800 W to 2000 W), via DMX

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- DMX channels: 34
- Setting and addressing: LCD display or remotely

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: Auto-sensing 190-245 V, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 5.5-11.3 A at 240 V
- DMX data in/out: 3 pin and 5 pin locking XLR

OPTIONS

- Matrioshka, outdoor dom (# 9126)

