

iWash Flex



iWash Flex - # 9120/1
(1 unit in single flight case)
iWash Flex- # 9120/2
(2 unit in double flight case)

SPECIFICATIONS

- «Best Color»™ (**Exclusive Coemar Patent**): colors dynamically determine the output of the lamp, thus allowing an optimal level of light output to be maintained
- CMY color mixing
- 8 colors + open on 2 wheels
- Proportional CTO filter
- Barndoor framing system (**Exclusive Coemar Patent**): four internal independently variable axial blades with proportional rotation of the assembly through 45°
- Proportional Zoom 11° - 42°
- Dimmer
- Mechanical and electronic strobe (Zap effect), synchronized, random, pulse effect
- Modular design for easy maintenance and servicing
- Pan 500°, Tilt 252°, 16 bit

PHYSICAL SIZE

- Length: 545 mm (21.5 in)
- Width: 595 mm (23.4 in)
- Height: 820 mm (32.2 in), head straight up
- Weight: 49 kg (109 lbs)

LAMP AND BALLAST

- Type: Philips MSR 2000 SA
- Color temperature: 6000 Kelvin
- Color rendering index: >80
- Average lamp life: 750 hours
- Socket: GY 22
- Electronic ballast with Power Factor Correction
- Electronically adjustable lamp power (800 W to 2000 W), via DMX

CONTROL PROTOCOL AND PROGRAMMING

- USITT DMX512/1990
- DMX channels: 22
- Setting and addressing: LCD display or remotely

ELECTRICAL SPECIFICATIONS/CONNECTIONS

- AC power: 190-245 V, auto-sensing, 50/60 Hz, 2m (6.6 ft) integral cable without power plug
- Power consumption: 5.5-11.3 A at 240 V
- DMX data in/out: 3 pin and 5 pin locking XLR

OPTIONS

- Matrioshka, outdoor dome (# 9126)
- PC lens kit 5.5°(#KIT89)

