

SPECIFICATIONS

B

PHYSICAL

- Size (L x W x H) 490 x 165 x 190 mm (19.3 x 6.5 x 7.5 in)
- Weight 8 kg (17.5 lbs)

THERMAL

- Maximum ambient temperature (T_a) 40° C (104° F)
- Maximum surface temperature 60° C (140° F)

CONTROL AND PROGRAMMING

- Data pin-out 3-pin locking XLR, pin 1 shield, pin 2 cold (-), pin 3 hot (+)
- Control protocol USITT DMX-512 (1990)
- DMX channels 1/6

AC POWER

- Input 3-prong IEC male socket
- Maximum power and current 275 W, 1.2 A @ 230 V
- Primary fuse, EU version 2.5 AT / 250 V, P/N 05020010
- Primary fuse, US version 5.0 AT / 250 V, P/N 05020018
- Secondary fuse 2.0 AT / 250 V, P/N 05020009

INSTALLATION

- Minimum distance to combustible materials 0.1 m (4 in)
- Minimum distance to illuminated surfaces 0.3 m (12 in)
- Minimum clearance around fan and air vents 0.1 m (4 in)

ACCESSORIES

- MC-1 controller, EU 90718000
- MC-1 controller, US 90718100
- Osram 24V/250W ELC 50 h halogen lamp 97000104
- Philips 24V/250W ELC 500 h halogen lamp 97000107
- G-clamp 91602003
- Half-coupler clamp 91602005